



ಸ್ಯ ಮುಕ್ತ ವಿಶ್ವವಿದ್ಯಾನಿಲಯ
ಮುಕ್ತಗಂಗೋತ್ರಿ, ಮೈಸೂರು-570006
ಇಂಜಿನಿಯರಿಂಗ್ ವಿಭಾಗ

No: KSOU/ES/AE/92/2019-20

Date: 05.03.2020

ದರಪಟ್ಟಿ ಆಹ್ವಾನ ಪ್ರಕಟಣೆ

ವಿಷಯ: ವಿವಿವಿಲಯದ ವಿಜ್ಞಾನ ಭವನ ಮತ್ತು ಆಡಳಿತ ಭವನ ಕಟ್ಟಡಗಳಲ್ಲಿ ಕೆಲವು ದುರಸ್ತಿ ಕೆಲಸಗಳನ್ನು ನಿರ್ವಹಿಸುವುದರ ಬಗ್ಗೆ

ಉಲ್ಲೇಖ: ಮಾನ್ಯ ಕುಲಪತಿಗಳ ಅನುಮೋದನೆ ದಿನಾಂಕ: 14.02.2020

ಕರ್ನಾಟಕ ರಾಜ್ಯ ಮುಕ್ತ ವಿಶ್ವವಿದ್ಯಾನಿಲಯದ ಆವರಣದಲ್ಲಿನ ವಿಜ್ಞಾನ ಭವನ ಮತ್ತು ಆಡಳಿತ ಭವನ ಕಟ್ಟಡಗಳಲ್ಲಿ ಕೆಲವು ದುರಸ್ತಿ ಕೆಲಸಗಳನ್ನು ನಿರ್ವಹಿಸಲು ಉದ್ದೇಶಿಸಲಾಗಿರುತ್ತದೆ.

ಈ ಹಿನ್ನೆಲೆಯಲ್ಲಿ ಈ ಕೆಳಕಂಡ ಕ್ರಮ ಸಂಖ್ಯೆ: 01 ರಿಂದ 07ರ ವರೆಗೆ ನಮೂದಿಸಿರುವ ಕೆಲಸಗಳನ್ನು ನಿರ್ವಹಿಸಲು ದರಪಟ್ಟಿಯನ್ನು ಆಹ್ವಾನಿಸಲಾಗಿದ್ದು ಸದರಿ ಕೆಲಸಗಳನ್ನು ನಿರ್ವಹಿಸಲು ತಗಲುವ ವೆಚ್ಚದ ಕನಿಷ್ಠ ದರವನ್ನು (ನಿಯಮಾನುಸಾರ ಚಾಲ್ತಿ ವರ್ಷದ ತೆರಿಗೆಗಳನ್ನು ಒಳಗೊಂಡಂತೆ) ನಮೂದಿಸಿ ಮೊಹರು ಮಾಡಿದ ಲಕೋಟಿಯ ಮೇಲೆ “ವಿವಿವಿಲಯದ ವಿಜ್ಞಾನ ಭವನ ಮತ್ತು ಆಡಳಿತ ಭವನ ಕಟ್ಟಡಗಳಲ್ಲಿ ಕೆಲವು ದುರಸ್ತಿ ಕೆಲಸಗಳನ್ನು ನಿರ್ವಹಿಸುವ ಸಂಬಂಧದ ದರಪಟ್ಟಿ” ಎಂದು ನಮೂದಿಸಿ ಕುಲಸಚಿವರು, ಕರಾಮುವಿ, ಮೈಸೂರು ಇವರಿಗೆ ಮುದ್ದಾಗಿ/ಅಂಚೆ ಮೂಲಕ ದಿನಾಂಕ: **18.03.2020** ರ ಒಳಗೆ ಸಲ್ಲಿಸಲು ಕೋರಲಾಗಿದೆ.

Dear Sir,

Sub: Quotation for the work of Petty Repair work at Science Block, Administrative Block and VC's Official Residential House at KSOU campus, Mukthagangothri, Mysuru.

1. Sealed competitive quotation is invited by the undersigned for the following items of work.

SL. NO	DESCRIPTION	UNIT	QTY	RATE	AMOUNT
1	Providing and laying flooring using prepolished, water cut/gang saw 19mm thick granite laid over bed of 20mm thick 1:4 cm & jointed with neat cement slurry mixed with pigment to mach shade of granite slabs including laying POP on finished surface and cleaning the surface, including the cost of all materials and labours etc., complete as per specifications. - using silver grey granite / Multy Red / Ruby Red / Black / HassanGreen Granite of width not less than 1200mm				
2	Providing half nosing for 20mm thick granite slab using required machinery including cost and conveyance of all materials, labour for all items of work, HOM of equipment etc., complete as per specification				
3	Providing and Fixing Stainless Steelsink of sizes upto 40cms x 47cms in 20mm thick granite slab of by cutting required thickness and width of grooves and fixing using adhesives etc., complete including cost and conveyance of all materials, labour for all items of work, HOM with all lead and lift, loading and unloading, transportation charges and all other incidental charges etc., complete as per specification and directions of the Engineer-in-charge of the work.				

4	<p>Providing and fixing M.S. angle bottom & top 50x50x6mm double equal angles, welded back to back and in between top & bottom line, in areas of mid section is provided with 50x50x6mm equal single angle for vertical and inclined members and at supporting ends 40x40x5mm single angle is provided. All the members are welded together with 6mm gusset plate as per Drawing No.CBS/ SD/K-Mantap/9/MND/97. The entire truss is anchored in RCC column by using 4 Nos. of M.S. anchor bolts at each support, with 10mm thick base plate and shoe plate. The work includes cutting, straightening, placing in position of M.S angle and welding wherever necessary, and applying one coat of red oxide primer coat to all the members including cost of all materials, labour charges, & hire charges of machineries for cutting, welding, grinding & erection equipments, etc., complete as per specification</p>				
5	<p>PROVIDING TRAPEZOIDAL PROFILED SHEET Providing and installing of pre painted Galvalume iron Trapezoidal profiled sheet of approved make 1060 mm width (1000 mm cover width), 28-30 mm crest height with crest distance of 200 mm c/c with 2 ribs at the centre for stiffening. The total coated thickness (TCT) of the sheet will be 0.47 mm +/- 0.02 mm tolerance Zinc-Alu Alloy coating AZ150 gsm as per ASTM 1397/A755-550 mpa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyester top coat 20-22 microns using self drilling/self tapping screws of 25 mm length, to be fixed over the existing purlins, rafters, channels and trusses.</p>				
6	<p>Providing and fixing Vitrified glazed tiles of approved make, quality & colour of size 600 x 600 x 10mm thick fixed on existing flooring with special adhesive for flooring, skirting and jointed with neat cement slurry mixed with pigment to match shade of tiles, including providing spacers at required interval and removing stains, cost of materials, mortar, labour etc., complete as per specification.</p>				
7	<p>Providing and fixing Special make glazed Vitrified tiles (Granomite finish) of approved make, quality and colour of size 600x600x10mm thick fixed on existing flooring with a special roffe adhesive for flooring and skirting etc., complete including providing spacers at required interval and removing stains etc., complete.</p>				
					Sub Total Rs.
					GST @ 12% Rs.
					Grand Total Rs.

2. Quoted Price:

- (a) The tendered shall quote for items in the format of quotation attached;
- (b) The specification should be drafted to permit the widest possible competition and at the same time present a clear statement of the required standards of workmanship, materials, and performances of the goods to be procured.
- (c) Reference to Brand name and catalogue number should be avoided as far as possible. Where unavoidable, they should be followed by the words 'or at least equivalent'.
- (d) All duties, taxes and other levies payable by the tendered (including tax on the finished goods) shall be included in the rate.
- (e) The rates quoted for each item shall be fixed for the duration of the contract and shall not be subject to any adjustment.

cial quantity of an item are not acceptable.

all be made by crossing out, initialing, dating and

rewriting.

(h) Cable of facsimile quotations are not acceptable.

3. Each tender must submit only one quotation

4. Evaluation of quotations

(a) The purchaser will evaluate and compare the quotations determined to be substantially responsible i.e., which are properly signed, and conform to the terms and conditions and specifications in the following manger:

(b) The evaluation would be done for all the items put together. The items for which no rated have been quoted would be treated as Zero and the total amount would be computer accordingly. Purchaser will award the contract to the responsive tenderer, whose total cost for all the items put together is the lowest.

5. Award of Contract:

(a) The purchaser will be award the contract to the tenderer whose quotation has been determined to be substantially responsible and who has offered the lowest price as per para 4 (b) above.

(b) The purchaser reserve the right at the time of contract award to increase or decrease the quantities of any or all of the items indicated in Para I 25% without any change in the unit price or any terms and conditions.

(c) Normal commercial warranty/guarantee if available shall be applicable to the supplied goods;

(d) Payment shall be made after the delivery of the goods and their acceptance.

(e) Notwithstanding the above, the purchaser reserves the right to accept or reject any quotations and to cancel the quotation process and reject all quotations at any time prior to the award of the contract.

6. Last date and time of receipt of quotations:

You are requested to submit the sealed quotations super scribed on the envelope as "Quotations for the above due date on **18.03.2020** latest by 5.30 PM hours.

We look forward to receiving your quotations.

By Order

Registrar
KSOU, Mysuru

Attachment : Schedule of Quotation Form

ಪ್ರತಿ:-

1. ವಿಶೇಷ ಅಧಿಕಾರಿಗಳು, ಮಾನ್ಯ ಕುಲಪತಿಗಳ ಕಾರ್ಯಾಲಯ ಕರಾಮುವಿ, ಮೈಸೂರು ರವರಿಗೆ ಮಾಹಿತಿಗಾಗಿ,
2. ಕುಲಸಚಿವರ ಆಪ್ತ ಸಹಾಯಕರು, ಕರಾಮುವಿ, ಮೈಸೂರು
3. ನಿರ್ದೇಶಕರು, ಐಟಿ ವಿಭಾಗ, ಕರಾಮುವಿ, ಮೈಸೂರು ರವರಿಗೆ ಈ ಪ್ರಕಟಣೆಯನ್ನು ವಿವಿವಿಲಯದ ಅಧಿಕೃತ ವೆಬ್‌ಸೈಟ್ ನಲ್ಲಿ ದಿನಾಂಕ **18.03.2020** ರವರೆಗೆ ಪ್ರಟಿಸಲು ತಿಳಿಸಲಾಗಿದೆ.
3. ಕಛೇರಿ ಪ್ರತಿ.

Quotation Form

10,

Date:

The Registrar
KSOU, Mg,
Mysuru

Dear Sir,

Sub: Quotation for the work of Petty Repair work at Science Block, Administrative Block and VC's Official Residential House at KSOU campus, Mukthagangothri, Mysuru.

1. Sealed competitive quotation is invited by the undersigned for the following items of work.

SL. NO	DESCRIPTION	UNIT	QTY	RATE	AMOUNT
1	Providing and laying flooring using prepolished, water cut/gang saw 19mm thick granite laid over bed of 20mm thick 1:4 cm & jointed with neat cement slurry mixed with pigment to mach shade of granite slabs including laying POP on finished surface and cleaning the surface, including the cost of all materials and labours etc., complete as per specifications. - using silver grey granite / Multy Red / Ruby Red / Black / HassanGreen Granite of width not less than 1200mm				
2	Providing half nosing for 20mm thick granite slab using required machinery including cost and conveyance of all materials, labour for all items of work, HOM of equipment etc., complete as per specification				
3	Providing and Fixing Stainless Steelsink of sizes upto 40cms x 47cms in 20mm thick granite slab of by cutting required thickness and width of grooves and fixing using adhesives etc., complete including cost and conveyance of all materials, labour for all items of work, HOM with all lead and lift, loading and unloading, transportation charges and all other incidental charges etc., complete as per specification and directions of the Engineer-in-charge of the work.				
4	Fabricating, supplying & erecting M.S. angular Truss of span upto 10m. The bottom & top member is provided with 50x50x6mm double equal angles, welded back to back and in between top & bottom line, in areas of mid section is provided with 50x50x6mm equal single angle for vertical and inclined members and at supporting ends 40x40x5mm single angle is provided. All the members are welded together with 6mm gusset plate as per Drawing No.CBS/ SD/K-Mantap/9/MND/97. The entire truss is anchored in RCC column by using 4 Nos. of M.S. anchor bolts at each support, with 10mm thick base plate and shoe plate.The work includes cutting, straightening, placing in position of M.S angle and wleding wherever necessary, and applying one coat of red oxide primer coat to all the members including cost of all materials, labour charges, & hire charges of machinerries for cutting, welding, grinding & erection equipments, etc., complete as per specification				

		ROFILED re painted l sheet of				
5		approved make 1060 mm width (1000 mm cover width), 28-30 mm crest height with crest distance of 200 mm c/c with 2 ribs at the centre for stiffening. The total coated thickness (TCT) of the sheet will be 0.47 mm +/- 0.02 mm tolerance Zinc-Alu Alloy coating AZ150 gsm as per ASTM 1397/A755-550 mpa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyester top coat 20-22 microns using self-drilling/self-tapping screws of 25 mm length, to be fixed over the existing purlins, rafters, channels and trusses.				
6		Providing and fixing Vitrified glazed tiles of approved make, quality & colour of size 600 x 600 x 10mm thick fixed on existing flooring with special adhesive for flooring, skirting and jointed with neat cement slurry mixed with pigment to mach shade of tiles, including providing spacers at required interval and removing stains, cost of materials, mortar, labour etc., complete as per specification.				
7		Providing and fixing Special make glazed Vitrified tiles (Granomite finish) of approved make, quality and colour of size 600x600x10mm thick fixed on existing flooring with a special roffe adhesive for flooring and skirting etc., complete including providing spears at required interval and removing stains etc., complete.				
			Sub Total Rs,			
			GST @ 12% Rs,			
			Grand Total Rs,			

We agree to execute the above said work in accordance with the technical specifications for a total contract price _____ (in figures)
(Rupees _____
_____ (in words), within the period specified in the invitations of quotation.

Name : _____

Signature : _____

Date : _____