



ಸ್ಯ ಮುಕ್ತ ವಿಶ್ವವಿದ್ಯಾನಿಲಯ
ಮುಕ್ತಗಂಗೋತ್ರಿ, ಮೈಸೂರು-570006
ಇಂಜಿನಿಯರಿಂಗ್ ವಿಭಾಗ

No: KSOU/ES/AE/93/2019-20

Date: 18.05.2020

ದರಪಟ್ಟಿ ಆಹ್ವಾನ ಪ್ರಕಟಣೆ

ವಿಷಯ: ವಿವಿವಿಲಯದ ಗ್ರಂಥಾಲಯ ವಿಭಾಗದಲ್ಲಿನ ವೆದರ್‌ಫ್ರೂಫ್ ಹಾಗೂ ಹೆಡ್‌ರೂಮ್‌ನ ರೂಫಿಂಗ್ ಶೀಟ್‌ನ ದುರಸ್ತಿ ಕೆಲಸಗಳನ್ನು ನಿರ್ವಹಿಸುವುದರ ಬಗ್ಗೆ

ಉಲ್ಲೇಖ: ಮಾನ್ಯ ಕುಲಪತಿಗಳ ಅನುಮೋದನೆ ದಿನಾಂಕ: 15.02.2020

ಕರ್ನಾಟಕ ರಾಜ್ಯ ಮುಕ್ತ ವಿಶ್ವವಿದ್ಯಾನಿಲಯದ ಆವರಣದಲ್ಲಿನ ಗ್ರಂಥಾಲಯ ವಿಭಾಗದಲ್ಲಿನ ವೆದರ್‌ಫ್ರೂಫ್ ಹಾಗೂ ಹೆಡ್‌ರೂಮ್‌ನ ರೂಫಿಂಗ್ ಶೀಟ್‌ನ ದುರಸ್ತಿ ಕೆಲಸಗಳನ್ನು ನಿರ್ವಹಿಸಲು ಉದ್ದೇಶಿಸಲಾಗಿರುತ್ತದೆ.

ಈ ಹಿನ್ನೆಲೆಯಲ್ಲಿ ಈ ಕೆಳಕಂಡ ಕ್ರಮ ಸಂಖ್ಯೆ: 01 ರಿಂದ 03ರ ವರೆಗೆ ನಮೂದಿಸಿರುವ ಕೆಲಸಗಳನ್ನು ನಿರ್ವಹಿಸಲು ದರಪಟ್ಟಿಯನ್ನು ಆಹ್ವಾನಿಸಲಾಗಿದ್ದು ಸದರಿ ಕೆಲಸಗಳನ್ನು ನಿರ್ವಹಿಸಲು ತಗಲುವ ವೆಚ್ಚದ ದರವನ್ನು (ನಿಯಮಾನುಸಾರ ಚಾಲ್ತಿ ವರ್ಷದ ತೆರಿಗೆಗಳನ್ನು ಒಳಗೊಂಡಂತೆ) ನಮೂದಿಸಿ ಮೊಹರು ಮಾಡಿದ ಲಕೋಟಿಯ ಮೇಲೆ “ವಿವಿವಿಲಯದ ಗ್ರಂಥಾಲಯ ವಿಭಾಗದಲ್ಲಿನ ವೆದರ್‌ಫ್ರೂಫ್ ಹಾಗೂ ಹೆಡ್‌ರೂಮ್‌ನ ರೂಫಿಂಗ್ ಶೀಟ್‌ನ ದುರಸ್ತಿ ಕೆಲಸಗಳನ್ನು ನಿರ್ವಹಿಸುವ ಸಂಬಂಧದ ದರಪಟ್ಟಿ” ಎಂದು ನಮೂದಿಸಿ ಕುಲಸಚಿವರು, ಕರಾಮುವಿ, ಮೈಸೂರು ಇವರಿಗೆ ಖುದ್ದಾಗಿ/ಅಂಚೆ ಮೂಲಕ ದಿನಾಂಕ: ರ ಒಳಗೆ ಸಲ್ಲಿಸಲು ಕೋರಲಾಗಿದೆ.

Dear Sir,

Sub: Quotation for the work of repairing existing weather proof and providing roof sheet for head rooms of Library Block at KSOU Campus, Mukthagangothri, Mysuru.

1. Sealed competitive quotation is invited by the undersigned for the following items of work.

SL. NO	DESCRIPTION	UNIT	QTY	RATE/ UNIT	AMOUNT
1	Providing and laying flooring 40 mm thick, with an under layer of 30mm thick M-15 cement concrete, using broken granite metal of 12.5mm nominal size and top layer of 10mm thick plaster with cement mortar 1:3, finished with floating coat of neat cement , including cost of materials, labour, curing, complete as per specifications	Sqm	30.00		
2	Fabricating, supplying and erecting M.S. TubularTruss of span upto 10m. The bottom and top member is provided with 50x50x6mm double equal angles, welded back to back and in between top and bottom line, in areas of mid section is provided with 50x50x6mm equal single angle for vertical and inclined members and at supporting ends 40x40x5mm single angle is provided. All the members are welded together with 6mm gusset plate as per Drawing. The entire truss is anchored in RCC column by using 4 Nos. of M.S. anchor bolts at each support, with 10mm thick base plate and shoe plate.The work includes cutting, straightening, placing in position of M.S angle and welding wherever necessary, and applying one coat of red oxide primer coat to all themembers including cost of all materials, labour charges, and hire charges of machineries for cutting, welding, grinding and erection equipments, with all lead and lift, transportation, etc., complete as per specification.	Kg	172.48		
3	PROVIDING TRAPEZOIDAL PROFILED SHEET Providing and installing of pre painted Galvolume iron Trapezoidal profiled sheet of approved make 1060 mm width (1000 mm cover width), 28-30 mm crest height with crest distance of 200 mm c/c with 2 ribs at the centre for stiffening. The total coated thickness (TCT) of the sheet will be 0.47 mm +/- 0.02 mm tolerance Zinc-Alu Alloy coating AZ150 gsm as per ASTM 1397/A755-550 mpa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyester top coat 20-22 microns using self drilling/self tapping screws of 25 mm length, to be fixed over the existing purlins, rafters, channels and trusses.	Sqm	68.36		
				Sub Total Rs.	
				GST @ 12% Rs.	
				Grand Total Rs.	

te for items in the format of quotation attached;

- (b) The specification should be drafted to permit the widest possible competition and at the same time present a clear statement of the required standards of workmanship, materials, and performances of the goods to be procured.
 - (c) Reference to Brand name and catalogue number should be avoided as far as possible. Where unavoidable, they should be followed by the words 'or at least equivalent'.
 - (d) All duties, taxes and other levies payable by the tendered (including tax on the finished goods) shall be included in the rate.
 - (e) The rates quoted for each item shall be fixed for the duration of the contract and shall not be subject to any adjustment.
 - (f) Rates for supply of partial quantity of an item are not acceptable.
 - (g) Corrections if any shall be made by crossing out, initialing, dating and rewriting.
 - (h) Cable of facsimile quotations are not acceptable.
3. Each tender must submit only one quotation
 4. Evaluation of quotations
 - (a) The purchaser will evaluate and compare the quotations determined to be substantially responsible i.e., which are properly signed, and conform to the terms and conditions and specifications in the following manner:
 - (b) The evaluation would be done for all the items put together. The items for which no rates have been quoted would be treated as Zero and the total amount would be computed accordingly. Purchaser will award the contract to the responsive tenderer, whose total cost for all the items put together is the lowest.
 5. Award of Contract:
 - (a) The purchaser will award the contract to the tenderer whose quotation has been determined to be substantially responsible and who has offered the lowest price as per para 4 (b) above.
 - (b) The purchaser reserves the right at the time of contract award to increase or decrease the quantities of any or all of the items indicated in Para I 25% without any change in the unit price or any terms and conditions.
 - (c) Normal commercial warranty/guarantee if available shall be applicable to the supplied goods;
 - (d) Payment shall be made after the delivery of the goods and their acceptance.
 - (e) Notwithstanding the above, the purchaser reserves the right to accept or reject any quotations and to cancel the quotation process and reject all quotations at any time prior to the award of the contract.
 6. Last date and time of receipt of quotations:

You are requested to submit the sealed quotations super scribed on the envelope as
"Quotations for the above due date on _____ latest by 5.30 PM hours.

We look forward to receiving your quotations.

Registrar

Attachment : Schedule of Quotation Form

ಪ್ರತಿ:-

1. ವಿಶೇಷ ಅಧಿಕಾರಿಗಳು, ಮಾನ್ಯ ಕುಲಪತಿಗಳ ಕಾರ್ಯಾಲಯ ಕರಾಮವಿ, ಮೈಸೂರು ರವರಿಗೆ ಮಾಹಿತಿಗಾಗಿ,
2. ಕುಲಸಚಿವರ ಆಪ್ತ ಸಹಾಯಕರು, ಕರಾಮವಿ, ಮೈಸೂರು
3. ನಿರ್ದೇಶಕರು, ಐಟಿ ವಿಭಾಗ, ಕರಾಮವಿ, ಮೈಸೂರು ರವರಿಗೆ ಈ ಪ್ರಕಟಣೆಯನ್ನು ವಿವಿಲಿಯದ ಅಧಿಕೃತ ವೆಬ್‌ಸೈಟ್ ನಲ್ಲಿ ದಿನಾಂಕ _____ ರವರೆಗೆ ಪ್ರಚಟಿಸಲು ತಿಳಿಸಲಾಗಿದೆ.
3. ಕಛೇರಿ ಪ್ರತಿ.

Quotation Form

10,

Date:

The Registrar
KSOU, Mg,
Mysuru

Dear Sir,

Sub: Quotation for the work of repairing existing weather proof and providing roof sheet for head rooms of Library Block at KSOU Campus, Mukthagangothri, Mysuru.

1. Sealed competitive quotation is invited by the undersigned for the following items of work.

SL. NO	DESCRIPTION	UNIT	QTY	RATE/ UNIT	AMOUNT
1	Providing and laying flooring 40 mm thick, with an under layer of 30mm thick M-15 cement concrete, using broken granite metal of 12.5mm nominal size and top layer of 10mm thick plaster with cement mortar 1:3, finished with floating coat of neat cement , including cost of materials, labour, curing, complete as per specifications	Sqm	30.00		
2	Fabricating, supplying and erecting M.S. TubularTruss of span upto 10m. The bottom and top member is provided with 50x50x6mm double equal angles, welded back to back and in between top and bottom line, in areas of mid section is provided with 50x50x6mm equal single angle for vertical and inclined members and at supporting ends 40x40x5mm single angle is provided. All the members are welded together with 6mm gusset plate as per Drawing. The entire truss is anchored in RCC column by using 4 Nos. of M.S. anchor bolts at each support, with 10mm thick base plate and shoe plate.The work includes cutting, straightening, placing in position of M.S angle and wleding wherever necessary, and applying one coat of red oxide primer coat to all themembers including cost of all materials, labour charges, and hire charges of machineris for cutting, welding, grinding and erection equipments, with all lead and lift, transportation, etc., complete as per specification.	Kg	172.48		
3	PROVIDING TRAPEZOIDAL PROFILED SHEET Providing and installing of pre painted Galvolume iron Trapezoidal profiled sheet of approved make 1060 mm width (1000 mm cover width), 28-30 mm crest height with crest distance of 200 mm c/c with 2 ribs at the centre for stiffening. The total coated thickness (TCT) of the sheet will be 0.47 mm +/- 0.02 mm tolerance Zinc-Alu Alloy coating AZ150 gsm as per ASTM 1397/A755-550 mpa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyester top coat 20-22 microns using self drilling/self tapping screws of 25 mm length, to be fixed over the existing purlins, rafters, channels and trusses.	Sqm	68.36		
				Sub Total Rs.	
				GST @ 12% Rs.	
				Grand Total Rs.	

We agree to execute the above said work in accordance with the technical specifications for a total contract price _____ (in figures)

(Rupees _____)

_____ (in words), within the period specified in

the invitations of quotation.

Name : _____

Signature : _____

Date : _____